Technical Data Specifications



PELTOR

3M[™] PELTOR[™] Adapter FL4000-50 Series

Product Description

The 3MTM PELTORTM Adapter FL4000-50 Series Push-to-Talk (PTT) connects and provides push-to-talk functionality between 3MTM PELTORTM Communications Headsets and selected 2-way communication radios. The FL4000-50 Series PTT adapters are small in size, intrinsically safe (ATEX & IECEx approved), and offer distinct ergonomic feedback when the Push-to-Talk button is pressed. The FL4000-50 PTT Adapter series features Automatic Radio Jack Detection that reroutes audio back to the radio when the headset is disconnected from the adapter¹.

1: Supported on selected radios compatible with Jack Detection feature.

Key Features:

- ATEX / IECEx approved
- Small ergonomic design
- Automatic Radio Jack Detection

Applications:

The 3MTM PELTORTM Adapter FL4000-50 Series Push-to-Talk (PTT) is designed to be used with a 3MTM PELTORTM Headset and a 2-way radio in industrial areas where intrinsic safety is required.

Standards and Approvals:

3M[™] PELTOR[™] Adapter FL4000-50 Series Push-to-Talk (PTT) is in conformity with the provisions set out in the EMC directive 2004/108/EC, the RoHS directive 2011/65/EU and the ATEX directive 94/9/EC. Thereby it fulfils the requirements for CE marking. The product has been tested and approved in accordance with EN 61000-6-2:2005, EN 50581:2011, EN 50303:2000, EN 60079-0:2012 and EN 60079-11:2012.

Product marking:



I M1 Ex ia I



II 2G Ex ia IIC T4 Ga -20° C \leq Ta \leq +50 $^{\circ}$ C

Standard Models:

| Article number | Description | 3M ID number |
|----------------|---|--------------|
| FL4030-50 | 3M™ PELTOR™ Adapter PTT for Motorola GP340 | XH001680806 |
| PMLN6803A | 3M™ PELTOR™ Adapter PTT for Motorola DP4000Ex | XH001680848 |
| FL40107-50 | 3M™ PELTOR™ Adapter PTT for Kenwood Multipin | XH001680830 |

Technical data specifications

| Materials: | Polyamide with glass fiber reinforcement | | |
|---------------------------------|--|--|--|
| Weight: | 144 g | | |
| Colour: | Blue | | |
| Size PTT house: | 67x55x47mm | | |
| Use and storage: | Storage temperature: -20°C to +50°C, humidity <85% | | |
| Usage temperature: | -20°C to +55°C | | |
| Maximum recommended shelf life: | 5 years | | |

FL4030-50

PMLN6803A Motorola

Use limitation: Never modify or alter this product



3M Personal Safety Division 3M Svenska AB, Box 2341 SE-331 02 Värnamo Sweden

Internet: www.3M.com/PELTOR



